

## E-17



The impressive design, hard glass protection and smart multimedia features essential for professional and public environments.

The E-17 is a feature-rich, high resolution 17" LCD display well suited for small office/home office environments, classrooms, libraries, or retail spaces requiring multimedia displays with distinctive modern design. NeoV™ Optical Glass protects the display from scratches, accidents and incidental damage. Built-in speakers provide crisp sound for multimedia interaction, and an easy-access headphone jack allows for convenient independent listening. Built with the highest quality components, the E-17 is the optimum display for professional environments.

- > NeoV™ Optical Glass
- > Modern exterior
- > Unique rear cover on backside of display
- > Swift 3 ms response time
- > Crisp 800:1 contrast ratio
- > High 300 cd/m<sup>2</sup> brightness
- > Dual digital and analogue inputs
- > Built-in speakers
- > Side-panel headphone jack
- > Auto-adjustment for optimal settings
- > Intuitive OSD with key lock function
- > Kensington® security socket
- > VESA standard wall mount
- > Fold away base for quick storage



NeoV™ Optical Glass - The most trusted hard glass protection available. Only on AG Neovo displays



# E-17

Specifications		E-17
Panel	Panel Type	TFT LCD
	Panel Size	17.0" (432 mm)
	Max. Resolution	SXGA 1280 x 1024
	Pixel Pitch	0.264 mm
	Brightness	300 cd/m <sup>2</sup> (Typical)
	Contrast Ratio	800:1 (Typical)
	Viewing Angle (H/V)	160°/160° (Typical)
	Display Colour	16.2M
	Response Time	3 ms (GTG)
Panel Life Time	50,000 hrs (Minimum)	
Frequency (H/V)		H: 30 kHz - 80 kHz V: 56 Hz - 75 Hz
Max. Pixel Clock		140 MHz
Input	Analogue	15-Pin D-Sub
	Digital	24-pin DVI-D
Audio	Audio In	3.5 mm Audio Line-in
	Audio Out	3.5 mm Headphone Jack
	Speaker	2W x 2
Power	AC-DC Adaptor	External
	Power	AC 100 - 240 V, 50 - 60 Hz
	Consumption	< 48 W (On) < 2 W (Stand-by) < 1 W (Off)
NeoV™ Optical Glass	Thickness	3.0 mm (0.12")
	Reflection Rate	< 1%
	Transmission Rate	> 96%
	Coating Hardness	> 9H
Plug & Play	VESA	DDC 2B
Operating Conditions	Temperature	0 °C ~ 40 °C
	Humidity	10% ~ 90%
Storage Conditions	Temperature	-20 °C ~ 60 °C
	Humidity	5% ~ 95%
Mounting	VESA FPMPMI	Yes (100 mm)
Tilt	Tilt	+5° ~ +25°
Dimensions	Product (W x H x D)	400 x 393 x 171 mm (16" x 15.7" x 6.8")
	Packaging (W x H x D)	555 x 580 x 171 mm (21.9" x 22.8" x 6.7")
	Weight	Product Weight Packaged Product Weight
Regulation Approval	Certifications & Compliance	UL/CUL, TUV/Baurt, CB, GOST-R, FCC, CE, BSMI, WEEE, RoHS, Vista/Basic, PAT, REACH
Accessories	Supplied	Quick Guide, CD ROM (user manual and drivers), audio cable, power adaptor, power cord, 15-Pin D-Sub cable, 24-Pin DVI-D cable



Impressive modern exterior and slim design



NeoV™ Optical Glass protects against scratches, impacts and other physical damage



DVI input, built-in speakers and easy access headphone jack for multimedia and interactive applications



VESA standard wall mount allows for secure mounting almost anywhere