

X-17



A brilliant display that delivers advanced design, durability and versatile performance for progressive professional environments.

The X-17 is a highly durable 17" display that will deliver decades of performance. Featuring NeoV™ Optical Glass, built-in video support and multiple input options, the X-17 is well suited to professional public environments. The strong metal casing and VESA compatible wall mounts allows the X-17 to be mounted just about anywhere. The unique look and versatility of the X-17 make it the perfect display solution for any modern environment.

- > NeoV™ Optical Glass
- > Durable metal casing
- > Swift 3 ms response time
- > Crisp 3000:1 dynamic contrast ratio
- > S-Video and CVBS inputs
- > DVI video inputs for high quality signal
- > Hot key for preferred video mode: User, Text, Movie, Game, and Graphic
- > Auto-adjustment for optimal settings
- > Kensington® security socket
- > VESA standard wall mount
- > Available colours: black, white



NeoV™ Optical Glass - The most trusted hard glass protection available. Only on AG Neovo displays



X-17

Specifications		X-17
Panel	Panel Type	TFT LCD
	Panel Size	17.0" (432 mm)
	Max. Resolution	SXGA 1280 x 1024
	Pixel Pitch	0.264 mm
	Brightness	300 cd/m ² (Typical)
	Contrast Ratio	3000:1 (DCR)
	Viewing Angle (H/V)	160°/160° (Typical)
	Display Colour	16.2M
	Response Time	3 ms (GTG)
Panel Life Time	50,000 hrs (Minimum)	
Frequency (H/V)		H: 30 kHz - 80 kHz V: 56 Hz - 75 Hz
Max. Pixel Clock		140 MHz
Input	Analogue	15-Pin D-Sub
	Digital	24-Pin DVI-D
	S-Video	4-Pin Mini Din S-Video
	CVBS	CVBS Jack
Power	AC-DC Adaptor	External
	Power Consumption	AC 100 - 240 V, 50 - 60 Hz < 42 W (on) < 2 W (Stand-by) < 1 W (Off)
NeoV™ Optical Glass	Thickness	3.0 mm (0.12")
	Reflection Rate	< 1%
	Transmission Rate	> 96%
	Coating Hardness	> 9H
Plug & Play	VESA	DCC 2B, DCC/CI
Operating Conditions	Temperature	0 °C ~ 40 °C
	Humidity	10% ~ 90%
Storage Conditions	Temperature	-20 °C ~ 60 °C
	Humidity	5% ~ 95%
Mounting	VESA FPMPMI	Yes (100 mm)
Tilt	Tilt	0° ~ +15°
Dimensions	Product (W x H x D)	408 x 398 x 175 mm (16.1" x 15.7" x 6.9")
	Packaging (W x H x D)	513 x 493 x 226 mm (20.5" x 19.7" x 9.0")
Weight	Product Weight	6.8 kg (13.9 lbs)
	Packaged Product Weight	9.5 kg (20.9 lbs)
Regulation Approval	Certifications & Compliance	UL/CUL, TUV/Baurt, CB, GOST-R, FCC, CE, BSMI, WEEE, RoHS, Vista/Basic, REACH
Accessories	Supplied	Quick Guide, CD ROM (user manual and drivers), power cord, power adaptor, 15-Pin D-Sub cable, 24-Pin DVI-D cable, S-Video cable, CVBS cable



Available in black or white



Front-panel keypad with Input Select, Screen Menu, Contrast and Brightness controls for quick adjustments



Wide range of I/O connectors for flexibility and expandability in endoscopic video installations



NeoV™ Optical Glass and durable metal casing for water, dust and scratch resistance