



# SAMTRON 78E

Samsung CDT Monitor



The SAMTRON 78E is a renovated design product with the OSD control buttons dramatically moved to the right panel. The 78E is ergonomically engineered, and utilizing a Multi-Layer Coating, safe for eyes proven to be the best environment friendly monitor with TCO' 03 certification, the slim and ergonomic design of the 78E will increase your perception.

# SAMTRON 78E

## Samsung CDT Monitor



### sRGB



Standard Red Green Blue (sRGB) is a defined default color space. If a monitor, printer and scanner are all calibrated to the sRGB color characteristics.

### TCO '03



TCO certification is granted only to high level products that have passed stringent tests in the evaluation of picture quality, environment-friendliness, and user convenience. Samsung has again renewed its TCO certification for the SyncMaster in 2003. Rest assured that Samsung monitors are environmentally friendly and safe.

Rest assured that Samsung monitors are environmentally friendly and safe.

### True Compatibility



Designed for  
Microsoft®  
Windows®XP  
Windows®2000  
Windows®Me

The SyncMaster is compatible with any computer, whether you're using a Mac or WindowsXP/2000/ME/98.

### Plug & Play Compatibility



Plug in a device and use it, without worrying about configuring components.

### Multimedia Stand



A stand-type Audio System without extra personal speakers, the Multimedia lets you easily experience the dynamic sound of multimedia entertainment! (Option)

### Dimensions(unit:mm)



### Specifications Summary

CDT	Size	17" (16.0" Viewable)
	Face	FST
	Deflection	90°
	Pitch	0.23mm(H)
	Surface treatment	Multi-Layer Coating
Input Signal	Video signal	RGB Analog
	Sync signal	Separate H/V
	Horizontal Frequency	30 - 70kHz
	Vertical Frequency	50 - 160Hz
	Pixel Frequency	110MHz
Resolution	Signal Connection	15pin D-Sub
	Max. (based on VESA GTF Timing)	1,280 x 1,024 @65Hz
		1,152 x 864 @77Hz
		1,024 x 768 @86Hz
		800 x 600 @109Hz
Recommended	640 x 480 @134Hz	
Display Size	1,024 x 768 @85Hz	
	Typical(mm)	312 x 234
Mode	Max(mm)	325 x 244
	Factory/User	3/8 modes
Power	Supply	AC90-264VAC, 50/60Hz
	Consumption(nominal)	80W
	Power Management	≤ 2W @Off State
	Regulation	EPA/VESA DPMS
User Control	Display Director™	Brightness, Contrast, H/V-Moire
		Degauss, Reset
		Color Temperature (6500K/9300K)
		Color (Red, Green, Blue)
		sRGB
		H-Position, V-Position
		H-Size, V-Size
		Pincushion, Pinbalance
		Trapezoid, Parallelogram
		Rotation
Feature	Plug & Play	DDC 2B/2Bi
Regulation	Safety & X-ray	UL, CSA, TUV, CB, NEMKO, Korea EK, CCIB, PSB, NOM, GOST, CDRH, IRAM
	EMC	FCC, CE, VCCI, C-tick, BSMI, Mic, ICES
	Environmental/Ergonomics	TUV GS, MPR II, TCO '03 (Option)
	Windows Logo	Windows2000/ME/XP
Set Size	Set(WxDxH) [mm]	401x410x378
Weight	Set/Box	13.8kg / 15.3kg
Accessory	Software Kit	Install Driver
		Manual



\* Design and specifications are subject to change without notice

www.samsung-monitor.com

Distributed by:

