

New AQ series: Waterproof FAN

ANY IP RATING CAN BE SATISFIED

This fan submersion at specified depth exceeding 1 meter and no harmful ingress of water!



Specification: IP 55



- ▶ Protected from total touch protection and no harmful ingress of dust.
- ▶ Protected from water jets, from any directions and no harmful ingress of water.



New

Specialist in Thermal Solution System

Bearing type: =Ball =Sleeve - 1B1S =Hypro bearing

| PHOTO | Frame size | Model No. | Bearing Type | Voltage (v) | Current (A) | Power (W) | Speed (rpm) | AirFlow (CFM) | AirFlow (CMM) | Pressure (mmAq) | Pressure (InHzO) | Noise (dB/A) | Weight (g) |
|-------|--------------|-------------------|--------------|-------------|-------------|-----------|-------------|---------------|---------------|-----------------|------------------|--------------|------------|
| | 60x60x25mm | AQ0612HB-A70GL(T) | | 12 | 0.23 | 2.76 | 4500 | 23.2 | 0.656 | 4.78 | 0.191 | 32.3 | 58 |
| | | AQ0612MB-A70GL(T) | | 12 | 0.14 | 1.68 | 3500 | 18.0 | 0.509 | 3.00 | 0.120 | 24.0 | |
| | | AQ0612LB-A70GL(T) | | 12 | 0.08 | 0.96 | 2500 | 13.2 | 0.373 | 1.60 | 0.064 | 16.1 | |
| | 80x80x25mm | AQ0812HB-A70GL(T) | | 12 | 0.25 | 3.00 | 3000 | 38.6 | 1.092 | 3.81 | 0.152 | 33.0 | 82 |
| | | AQ0812MB-A70GL(T) | | 12 | 0.15 | 1.80 | 2500 | 32.9 | 0.931 | 2.85 | 0.114 | 28.3 | |
| | | AQ0812LB-A70GL(T) | | 12 | 0.12 | 1.44 | 2100 | 27.6 | 0.781 | 1.95 | 0.078 | 22.5 | |
| | | AQ0812DB-A70GL(T) | | 12 | 0.08 | 0.96 | 1600 | 20.5 | 0.580 | 1.27 | 0.051 | 15.0 | |
| | | AQ0824HB-A70GL(T) | | 24 | 0.16 | 3.84 | 3200 | 40.0 | 1.132 | 4.28 | 0.171 | 35.0 | |
| | | AQ0824MB-A70GL(T) | | 24 | 0.10 | 2.40 | 2400 | 30.0 | 0.849 | 2.50 | 0.100 | 27.0 | |
| | | AQ0824LB-A70GL(T) | | 24 | 0.09 | 2.16 | 2200 | 29.0 | 0.820 | 2.07 | 0.083 | 24.0 | |
| | 92x92x25mm | AQ0912HB-A70GL(T) | | 12 | 0.25 | 3.00 | 2900 | 52.5 | 1.485 | 3.32 | 0.133 | 35.0 | 103 |
| | | AQ0912MB-A70GL(T) | | 12 | 0.17 | 2.04 | 2400 | 43.5 | 1.231 | 2.30 | 0.092 | 31.3 | |
| | | AQ0912LB-A70GL(T) | | 12 | 0.13 | 1.56 | 2050 | 36.0 | 1.018 | 1.57 | 0.063 | 25.0 | |
| | | AQ0924HB-A70GL(T) | | 24 | 0.15 | 3.60 | 2900 | 52.5 | 1.485 | 3.28 | 0.131 | 35.0 | |
| | | AQ0924MB-A70GL(T) | | 24 | 0.12 | 2.88 | 2500 | 45.0 | 1.273 | 2.38 | 0.095 | 31.5 | |
| | | AQ0924LB-A70GL(T) | | 24 | 0.08 | 1.92 | 2300 | 41.6 | 1.177 | 2.18 | 0.087 | 29.8 | |
| | 120x120x25mm | AQ1212HB-A71GL | | 12 | 0.37 | 4.44 | 2200 | 85.2 | 2.410 | 3.45 | 0.138 | 39.1 | 164 |
| | | AQ1212MB-A71GL | | 12 | 0.33 | 3.96 | 2050 | 80.5 | 2.277 | 2.97 | 0.119 | 38.0 | |
| | | AQ1212LB-A71GL | | 12 | 0.24 | 2.88 | 1800 | 72.0 | 2.037 | 2.41 | 0.096 | 34.4 | |
| | | AQ1224HB-A71GL | | 24 | 0.19 | 4.56 | 2200 | 85.2 | 2.410 | 3.45 | 0.138 | 39.1 | |
| | | AQ1224MB-A71GL | | 24 | 0.17 | 4.08 | 2050 | 80.5 | 2.277 | 2.97 | 0.119 | 38.0 | |
| | | AQ1224LB-A71GL | | 24 | 0.14 | 3.36 | 1800 | 72.0 | 2.037 | 2.41 | 0.096 | 34.4 | |

2 wires, 3rd wire available

Specifications subject to changewithout notice

ADDA CORPORATION.

© COPYRIGHT 2002 ADDA CORPORATION. ALL RIGHT RESERVED.
ALL OTHER TRADEMARKS AND/OR SERVICE MARKS LISTED IN
THIS PUBLICATION ARE THE PROPERTY OF THEIR RESPECTIVE OWNERS.

TEL.886-8-753 9178~9 FAX.886-8-753 2815

URL.HTTP://www.adda.com.tw

E-MAIL.addacorp@ms2.hinet.net