Blu-ray Combo Drive

Visit our website:
www.sonynec-optiarc.eu

2x Slimline BD Combo:

BC-5500A/BC-5500S

Two lightweight multi-talents: BC-5500A and BC-5500S are ideal for a combined application by reading Blu-ray Discs and writing to DVDs and CDs. Profit from perfect functionality within the most compact form. Available as P-ATA and S-ATA variant.

- 2x fast BD reading for 25 GB BD-R, BD-RE and 50 GB dual layer R and RE Blu-ray Discs

- DVD and CD media compatibility:

  Read ▶ DVD: 8x max.   ▶ CD: 24x max.

  Write ▶ DVD ±R: 8x max.   ▶ CD-R: 16x max.
         ▶ DVD ±RW: 4x max.   ▶ CD-RW: 10x max.
         ▶ DVD-RAM: 5x max.

- Interface:
  BC-5500A: IDE/ATAPI interface (P-ATA)
  BC-5500S: high speed S-ATA interface

- 12 cm and 8 cm BD, DVD and CD media supported

- 0.2 kg lightweight

- Emergency eject

P-ATA
S-ATA

Optiarc

Blu-ray Combo Drive

2x Slimline BD Combo: BC-5500A/BC-5500S

Amazingly versatile: Read Blu-ray Discs – write to DVDs

Technical Specifications BC-5500A/BC-5500S		Blu-ray Disc	DVD	CD
Transfer Rate read		2x (max. 8,800 kByte/s)	8x (max. 10,800 kByte/s)	24x (max. 3,600 kByte/s)
Transfer Rate write	-R	./.	8x (max. 10,800 kByte/s)	16x (max. 2,400 kByte/s)
	-R DL	./.	4x (max. 5,400 kByte/s)	./.
	-RE/W	./.	4x (max. 5,400 kByte/s)	10x (max. 1,500 kByte/s)
	-RAM	./.	5x (max. 6,900 kByte/s)	./.
	+R	./.	8x (max. 10,800 kByte/s)	./.
	+R9	./.	4x (max. 5,400 kByte/s)	./.
	+RW	./.	4x (max. 5,400 kByte/s)	./.
Access Time		320 ms	200 ms	190 ms
Mechanism		Tray load mechanism		
Interface		BC-5500A: IDE / ATAPI (P-ATA) BC-5500S: S-ATA		
Media/Modes supported		BD-ROM, BD-R(DL), BD-RE(DL), DVD-ROM, DVD-R/-R DL/-RW, DVD +R/+R9/+RW, DVD-RAM, DVD-Video, CD-DA, CD-ROM (XA), CD Extra, Video CD, Photo CD, CD Text		
Weight		0.2 kg		
Dimensions		128 mm x 12.7 mm x 129 mm		

SERIAL ATA **Blu-ray Disc™** **DVD** **RW** **COMPACT disc**

Optiarc

**Visit our website:
www.sonynec-optiarc.eu**