

6x Slimline Slot-in BD Combo: BC-5640H

- Read Speed: BD 6x ,DVD 8x ,CD 24x
- Write Speed: DVD+/-R 8x max

DVD+R9:	6x max	DVD-R DL:	6x max
DVD+RW:	8x max	DVD-RW:	6x max
DVD-RAM:	5x max		
CD-R:	24x max	CD-RW:	16x max
- High speed S-ATA interface
- Slot-in BD/DVD/CD media load
- 12 cm media supported
- 0.16 kg lightweight



Specifications	6X slim slot-in S-ATA BD Combo (BC-5640H)		
	<u>Blu-ray Disc</u>	<u>DVD</u>	<u>CD</u>
Transfer Rate read	6x (max. 27 Mbytes/s)	8x (max. 11 Mbyte/s)	24x (max. 3600 kByte/s)
Transfer Rate write		8x (max. 11 Mbyte/s)	24x (max. 3600 kByte/s)
	-R	6x (max. 8.3 Mbyte/s)	./.
	-R DL	6x (max. 8.3 Mbyte/s)	./.
	-RW	6x (max. 8.3 Mbyte/s)	16x (max. 2400 kByte/s)
	-RAM	5x (max. 6.9 Mbyte/s)	./.
	+R	8x (max. 11 Mbyte/s)	./.
	+R9	6x (max. 8.3 Mbyte/s)	./.
	+RW	8x (max. 11 Mbyte/s)	./.
Access Time(Random)	230 msec	180 msec	190 msec
Mechanism	Slot loading mechanism		
Interface	S-ATA		
Burst Transfer Rate	150 MByte/s		
Cache Memory	5.8 Mbyte read ahead data buffer		
Media/Modes supported	BD-ROM, BD-AV, BD-R(DL), BD-RE(DL), DVD-ROM, DVD-R/R DL/-RW, DVD+R/+R9/+RW, DVD-RAM, DVD-V/Video; CD-DA, CD-ROM (XA), CD-RW, CD Extra, Video CD, Photo CD, CD Text		
Weight	0.16 kg without Bezel		
Dimensions	128mm(width) x 12.7mm(height) x 129mm(depth with bezel)		

